

GYROMAT 3000

Fully Automatic Precision Gyroscope

The GYROMAT instrument series is a range of high precision surveying gyroscopes with band suspension, which are the result of more than 60 years of experience in the development and manufacture of gyroscopic measuring instruments. The fully automatic measuring procedure and measurement technique that has no any preliminary orientation provide the greatest accuracy in determining direction in those areas in which other methods cannot be efficiently used, for example in mining and tunnelling.

The GYROMAT 3000 has for many years been a reliable instrument for measuring directions with an accuracy of 1/1000th gon, which corresponds to a deviation in arc of about 1.6 cm over a distance of one kilometre. The time needed for measuring a single direction is about 10 minutes.

This time can be reduced by applying two other survey programs, but the measuring accuracy is also reduced. The option to add a theodolite or a total station as required enables the instrument to be used universally for geodetic applications or control work.

GYROMAT 3000

- Maximum measuring accuracy
- Fast and fully automatic measurement sequence
- No need for pre-orientation
- Customer defined total station or theodolite set up



GYROMAT 3000

Special Design Features

- Ergonomically designed instrument with integrated batteries
- Three serial interfaces (RS 232) to connect to a PC, a total station or other devices
- Wireless remote control and data transmission
- Two operation panels with integrated multiline display and keyboard
- Menu-controlled, interactive operation
- Integrated monitoring plus comprehensive history and help functions

Technical specifications

Measuring modes	1	2	3
Measuring accuracy in mgon*	1	10	5
Measuring time in minutes (approx.)	10	2	5
Battery capacity for single measurements	25	50	35
Operating temperature	-20 °C up to + 50 °C (-12 °C up to + 45 °C calibrated)		
Area of application	Between 80° south latitude and 80° north latitude		
Dimension and weight:			
GYROMAT 3000 (without theodolite)	11.5 kg, 215 mm centering diameter		
Transport container	Weight: 26 kg, (LxWxH) 460x460x800 mm		
Tripod	Weight: 8 kg, 300 mm diameter		
*) Standard deviation ($\pm 1\sigma$) under lab conditions in accordance with DIN 18723			
Subject to technical changes			



Tunnel survey with GYROMAT 3000

DMT GmbH & Co. KG
 Am TÜV 1
 45307 Essen, Germany
 T +49 201 172-1441
 E products@dmf-group.com
gyromat.de

Disposal information: :
 Our products are subject to the WEEE directive.
 DMT has committed itself to take back all
 electrical and electronic components sold
 and to dispose of them professionally.
 Please contact: products@dmf-group.com

WEEE Registration Number: **DE 25917380**



DIN EN ISO 9001
 DIN EN ISO 14001
 DIN ISO 45001